

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : A61M 16/00, F24F 13/24	A1	(11) International Publication Number: WO 00/38771
		(43) International Publication Date: 6 July 2000 (06.07.00)

(21) International Application Number: PCT/AU99/01146

(22) International Filing Date: 22 December 1999 (22.12.99)

(30) Priority Data:
PP 7896 23 December 1998 (23.12.98) AU

(71) Applicant (for all designated States except US): RESMED LIMITED [AU/AU]; 97 Waterloo Road, North Ryde, NSW 2113 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): DANTANARAYANA, Muditha. Pradcep [AU/AU]; 21 Carole Avenue, Baulkham Hills, NSW 2153 (AU).

(74) Agent: SPRUSON & FERGUSON; G.P.O. Box 3898, Sydney, NSW 2001 (AU).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BE, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LI, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CN, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: AN APPARATUS FOR SUPPLYING BREATHABLE GAS

(57) Abstract

An apparatus (1) for supplying breathable gas is disclosed. The apparatus (1) includes a relatively rigid external housing (2), at least one noise producing component (3, 4, 5, 6) internal the housing (2), and a thin flexible enclosure (8) substantially sealed around the noise producing components (3, 4, 5, 6). A method of assembling the apparatus (1) is also disclosed. The method comprises the steps of assembling the noise producing component(s) (3, 4, 5, 6) into a sub-assembly, placing the sub-assembly into the interior (9) of the thin flexible enclosure (8) through an opening therein, substantially sealing the opening, and placing the flexible enclosure (8) within the external housing (2).

